

Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Restricted to professional users.
- · Application of the substance / the mixture Detergent
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Alfred Kärcher SE & Co. KG

Alfred-Kärcher-Str. 28-40 D - 71364 Winnenden Tel.: +49-7195-14-0

Kärcher (UK) Ltd.

Kärcher House Brookhill Way Banbury Oxon OX16 3ED Great Britain

Tel.: +44-1295-752-000

Internet: www.karcher.com

· Further information obtainable from:

Regulatory Affairs
Tel.: +49-7195-14-0
productsafety.management.de@karcher.com

1.4 Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1 H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 1)

· Hazard pictograms



· Signal word Danger

Hazard-determining components of labelling:

sodium hydroxide

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

Dangerous components:		
CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-xxxx	2-(2-butoxyethoxy)ethanol Eye Irrit. 2, H319	10-20%
CAS: 15763-76-5 EINECS: 239-854-6 Reg.nr.: 01-2119489411-37-xxxx	sodium p-cumenesulphonate © Eye Irrit. 2, H319	1-5%
CAS: 1310-73-2 EINECS: 215-185-5 Index number: 011-002-00-6 Reg.nr.: 01-2119457892-27-xxxx	sodium hydroxide	≥0.5-<2%
CAS: 31726-34-8	hexane-1-ol, ethoxylated (polymer)	1-5%

(Contd. on page 3)



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 2)

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information

Involve doctor immediately.

Immediately remove any clothing soiled by the product.

· After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- · After skin contact Immediately wash with water and soap and rinse thoroughly.
- After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- · 4.2 Most important symptoms and effects, both acute and delayed Corneal damage
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear fully protective suit.
- · Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 3)

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with eyes and skin.

- · Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility:

Do not store together with acids.

Keep away from food, beverages and feed.

- · Further information about storage conditions: Keep receptacle tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

	· Paramotoro			
Ingredients with limit values that require monitoring at the workplace:				
112-34-5 2-(2-butoxyethoxy)ethanol			
WEL Short- Long-t	WEL Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm			
1310-73-2 s	1310-73-2 sodium hydroxide			
WEL Short-	term value: 2 mg/m³			
· DNELs				
15763-76-5	sodium p-cumenesulphonate			
Oral D	NEL 3.8 mg/kg×d (consumer)			
Dermal D	NEL 136.25 mg/kg×d (employee)			
	68.1 mg/kg×d (consumer)			

(Contd. on page 5)



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

			Contd. of page 4)
Inhalative	DNEL	26.9 mg/m3 (employee)	
		6.6 mg/m3 (consumer)	
1310-73-2	sodiu	m hydroxide	
Inhalative	DNEL	1 mg/m3 (employee)	
		1 mg/m3 (consumer)	
·PNECs			
15763-76-	5 sodii	um p-cumenesulphonate	
PNEC		0.23 mg/l (freshwater)	
		0.023 mg/l (marine water)	
		100 mg/l (STP)	
PNEC sed	liment	0.862 mg/kg (freshwater)	
		0.086 mg/kg (marine water)	
PNEC soil		0.037 mg/kg (soil)	

- 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Do not inhale gases / fumes / aerosols.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A/P2.

· Hand protection



Protective gloves.

- · Material of gloves Butyl rubber, BR
- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable:
- * butyl rubber 0,7 mm, 480 min (EN 374)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Nitrile rubber. NBR
- · Eye/face protection



Tightly sealed goggles (EN 166)

(Contd. on page 6)



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 5)

· Body protection:

Apron **Boots**

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Physical state Liquid · Colour: Light yellow · Odour: fresh

· Odour threshold: Not determined.

• Melting point/freezing point: -7 °C Boiling point or initial boiling point and boiling range 100 °C

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. Flash point: Not applicable

· Auto-ignition temperature: not applicable Decomposition temperature: Not determined.

pH at 20 °C 13 · pH-value 1 %: 10-12

· Viscosity:

· Kinematic viscosity Not determined.

· dynamic at 20 °C: 3 mPas

· Solubility

· Water: Fully miscible · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined.

· Density and/or relative density

· Density at 20 °C: 1.063 g/cm³ Relative density Not determined. · Vapour density Not determined. · Relative gas density Not determined. Particle characteristics Not applicable.

9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

· Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

· Solvent content:

Solids content: 19.6 %

(Contd. on page 7)



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

		(Contd. of page 6)
· Change in condition		
· Evaporation rate	Not determined.	
Information with regard to physical hazard cla	sses	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
 Substances and mixtures, which emit flammable ga 	ases	
in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	May be corrosive to metals.	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity corresponds to 10.3
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Corrosive action on metals
Reacts with strong acids
Strong exothermic reaction with acids
Reacts with light alloys to form hydrogen
Corrodes aluminium

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Not compatible with alkali-sensitive substances like Sn, Zn, Al and paintings.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

– GI



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	· LD/LC50 values relevant for classification:				
	112-34-5 2-(2-butoxyethoxy)ethanol				
Oral	LD50	2410 mg/kg (mouse) (OECD 401)			
Dermal	Dermal LD50 2764 mg/kg (Rabbit)				
15763-7	15763-76-5 sodium p-cumenesulphonate				
Oral	LD50	>5000 mg/kg (Rat) (OECD 401)			
Dermal	LD50	>2000 mg/kg (Rabbit)			
	31726-34-8 hexane-1-ol, ethoxylated (polymer)				
Oral	LD50	>300-2000 mg/kg (Rat)			

- · Primary irritant effect:
- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:		
112-34-5 2-(2-but	oxyethoxy)ethanol	
LC50/96 h	1300 mg/l (Lepomis macrochirus)	
EC10/16 h	1170 mg/l (Pseudomonas putida)	
EC50/24 h	2850 mg/l (Daphnia magna) (DIN 38412)	
NOEC	>100 mg/l (Desmodesmus subspicatus)	
15763-76-5 sodiu	m p-cumenesulphonate	
LC50/96 h (static)	>100 mg/l (Oncorhynchus mykiss)	
EC50/48 h (static	>100 mg/l (Daphnia magna)	
EC50/96 h (static	>100 mg/l (Pseudokirchneriella subcapitata)	
	(Contd. on page 9	



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

	(Contd. of page 8)
1310-73-2 sodi	um hydroxide
LC50/96 h	125 mg/l (Gambusia affinis)
EC50/48 h	76 mg/l (Daphnia magna)
	40.4 mg/l (Ceriodaphnia dubia)
EC50/15 min	22 mg/l (Photobacterium phosphoreum)

· 12.2 Persistence and degradability No further relevant information available.

Degree of e	Degree of elimination:		
112-34-5 2-(2	2-butoxyethoxy)ethanol		
OECD 301C	80-90 % (28 d)		
OECD 301E	>70 % (28 d)		
OECD 302B	100 % (28 d)		

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

The product does not contain organically bounded halogens (AOX-free).

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

The contained organic complexing agents reach a DOC-elimination grade of 80% (corresponding to No. 406 of Annex "Analytic and measuring methods") and with this meet the tightened demands of Annex 49 of the revised Direction on liqid waste.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 9)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue

20 01 29* detergents containing hazardous substances

- Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Non contaminated packagings may be recycled.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

· Recommended cleansing agents: Water, if necessary together with cleaning agents.

SECTION 14: Transport information

• •	14	.1	UN	l num	ber	or l	ID	numl	ber
-----	----	----	----	-------	-----	------	----	------	-----

· ADR, IMDG, IATA UN1824

14.2 UN proper shipping name

· **ADR** 1824 SODIUM HYDROXIDE SOLUTION

· IMDG, IATA SODIUM HYDROXIDE SOLUTION

· 14.3 Transport hazard class(es)

· ADR



· Class 8 (C5) Corrosive substances.

· Label

· IMDG, IATA



· Class 8 Corrosive substances.

8

· Label

14.4 Packing group

· ADR, IMDG, IATA

(Contd. on page 11)



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

	(Contd. of page
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Corrosive substances.
Hazard identification number (Kemler code):	80
EMS Number:	F-A,S-B
Segregation groups	(SGG18) Alkalis
Stowage Category	A
Segregation Code	SG35 Stow "separated from" SGG1-acids
14.7 Maritime transport in bulk according to	IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1824 SODIUM HYDROXIDE SOLUTION, 8, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- National regulations
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)



Printing date 25.07.2025 Version number 8 (replaces version 7) Revision: 30.09.2022

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 11)

A product information sheet can be provided if requested.

· Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

Contact:

Regulatory Affairs Tel.: +49-7195-14-0

productsafety.management.de@karcher.com

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

· Sources

* Data compared to the previous version altered.

· 0·011-343·0 RM776/5 2·613

GB ·